

Catalytic Converter Seals



Description:

KnitMesh Technologies® seals are manufactured using mesh that is usually compressed in a die to make an even density all metal one piece end seal ring.

How They Work

They are designed to protect delicate ceramic honeycomb bricks and intumescent mats from gas erosion and to prevent exhaust gas bypass between the brick and the inner catalytic converter shell. They are also used extensively within diesel filter assemblies.

It is also possible to produce an assembly having two seals that fit around either end of the monolith brick that are joined by connecting mesh. This is particularly useful where the converter can design does not have any other way of keeping seals in position.

Components can be designed that maintain a constant seal as the filter and housing expand at different rates of thermal expansion. The seal can be designed to operate within its elastic range over this compression range.

Quality Assurance

KnitMesh Technologies® is accredited to ISO9001:2008, ISO14001:2004, OHSAS18001:2007, PAS 99:2006 and ISO/TS 16949:2009



Customer Support

KnitMesh Technologies

Greenfield, Flintshire, United Kingdom CH8 9DP
T +44 (0) 1352 717 600 F +44 (0) 1352 714 909 E sales@knitmeshtechnologies.com

Issue No 02 (02/11)

The information provided above is supplied in good faith and believed to be correct. This information is supplied upon the condition that persons receiving this will make their own determination as to its suitability for their purposes prior to use. KnitMesh makes no representations or warranties, either expressed or implied with respect to the information or the product to which this information refers.

Features and Benefits

- Low cost manufacture due to state of the art manufacturing techniques.
- Wide range of materials available to suit temperature requirements exceeding 1000°C.
- Seals can be produced to suit any size or shape of monolith brick.
- Round and oval cross sections available.
- Lips can be added for additional protection of monolith brick edges.
- Man-made materials such as silica yarns can be used in conjunction with a metal filament to improve performance.
- Prototypes can be produced cheaply and quickly from low cost die sets.
- Ceramic fibre materials can also be covered by mesh to give added protection against exhaust gas bypass.

 **KnitMesh Technologies®**
Innovative Mesh Solutions

www.knitmeshtechnologies.com